PRODUCT FACT SHEET



STYLUS PRO ALKALINE BATTERY-POWERED FLASHLIGHT

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive,

Sporting Goods, Consumer.

DESCRIPTION: The Stylus Pro® is a sleek compact pen sized, two AAA alkaline battery powered flashlight designed

> for use in all markets. It features a tail cap switch, momentary or constant on operation, a pocket clip for convenience, and amazing brightness and run time for a light of its size and price. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and

abrasion resistant.

CASE MATERIAL: Machined aluminum alloy case. Type II MIL-Spec anodized finish.

DIMENSIONS: Length: 5.3 in. (134 mm) Body Diameter: 0.60 in. (15 mm)

WEIGHT: 1.64 oz (46.9 grams) with batteries (included with purchase).

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 30,000 hour lifetime. - Solid body color models.

Nichia Ultra-Bright (Green) LED, with a 50,000 hour lifetime. - REALTREE HARDWOODS; Green and

Blaze Orange models.

LIGHT OUTPUT:

C4® White LED - 860 candela peak beam intensity, 58 meter beam distance and 90 lumens measured

system output.

Nichia Ultra-Bright Green LED - 73 candela peak beam intensity, 17 meter beam distance and 5

lumens measured system output.

ON/OFF:

Push button tail switch - momentary or constant on operation.

RUN TIME:



See chart for run time data. All runtime claims are to 10% of initial lumen output.

BATTERY: Two (2) "AAA" size, Alkaline batteries.

FEATURES: C4® LED technology for extreme brightness.

IPX4 rated for water resistant operation. All openings o-ring sealed.

1 meter impact resistance tested.

Removable pocket clip.

APPROVALS: (Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: N/A

OUTPUT

GREEN LED C4 WHITE LED 90 LUMENS LUMENS 6h 30min 11h 58m 17m 860cd 73cd

90.00

PERFORMANCE CURVE

HOURS

RUNTIME DISTANCE

INTENSITY

All performance claims to ANSI/NEMA FL1-2009 Standard Issued: 11/02/2007

Revised: 08/25/2015