



PRODUCT FACT SHEET

ProTac HL[®]4 HIGH LUMEN LITHIUM TACTICAL FLASHLIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION:

With 2,200 lumens of blinding light, the ProTac HL[®]4 is the newest and brightest addition to the ProTac[®] series. The ProTac HL[®]4 offers the latest in power LED technology and three different user selectable programs. The light will accept two battery types, four CR123A batteries or two Streamlight 18650 Li Ion rechargeable batteries. The output from the C4[®] LED results in one of the brightest tactical lights available. The “sure grip rubber sleeve” and included lanyard ensures you’ll never lose your grip.

CASE MATERIAL:

6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS:

Length: 8.63 in. (21.92 cm) Barrel Diameter: 1.24 in. (3.15 cm)
Head Diameter: 2.35 in. (5.97 cm) Tri-Lobe Diameter: 2.29 in. (5.81 cm)

WEIGHT:

1 lb 1 oz (482 grams) with CR123A batteries. 1 lb 2 oz (510 grams) with 18650 batteries.

LENS:

Glass lens with anti-reflective coating, gasket sealed.

LIGHT SOURCE:

C4[®] LED technology, impervious to shock with a 50,000 hour lifetime. Total internal reflection optic.

LIGHT OUTPUT:

See charts. Optimized electronics provides thermal management and regulated intensity.

ON/OFF:

Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP[®] programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/med/high.

RUN TIME:

See chart. All claims to 10% of initial lumen output.

BATTERY:

Four (4) 3 Volt CR123A Lithium batteries, (CR123A batteries have a shelf life of 10 years) or two Streamlight “Li Ion 18650 protected cylindrical 3.7V 2600 mAh rechargeable batteries that have their own cradle charging system.

FEATURES:



C4[®] LED technology for extreme brightness.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
1 meter impact resistance tested.
LED Solid State Power Regulation provides maximum light output throughout battery life.
TEN-TAP[®] programmable switch allows user to select one of three different programs.
Anti-roll facecap.
Sure grip rubber sleeve.
Serialized for positive identification.

WARRANTY:

Streamlight's Limited Lifetime Warranty

APPROVALS:

Meets applicable European Community directives.

OPTIONAL

ACCESSORIES:

Holster

	WITH CR123A BATTERIES			
	FL 1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		2200 LUMENS	600 LUMENS	60 LUMENS
RUNTIME		1h 30min	4h	40h
DISTANCE		346m	182m	56m
INTENSITY		30000cd	8300cd	800cd

Strobe Runtime: 2.5 hours

	WITH 18650 RECHARGABLE BATTERIES			
	FL 1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		2200 LUMENS	600 LUMENS	60 LUMENS
RUNTIME		1h 45min	4h 15min	43h
DISTANCE		346m	182m	56m
INTENSITY		30000cd	8300cd	800cd

Strobe Runtime: 3.5 hours

All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 1/7/2016

Revised: 1/11/2016

Rev: 1

Made In China

Document #278