

When you need maximum illumination with a wide beam to light a large area, the E-Flood LiteBox HL provides a blast of 5,300 lumens.



**5,300 LUMENS!**



6 LEDs and wide pattern parabolic reflectors produce a uniform flood pattern; optimized electronics provide regulated intensity	<b>Standard System</b> – International safety orange; includes shoulder strap, AC and DC charge cords, and mounting rack
3 levels of lighting: - High for a super-bright flood beam: 5,300 lumens; 42,000 candela; 410m beam distance; runs 1.75 hours - Medium for an intense beam and longer run time: 2,500 lumens; 21,300 candela; 292m beam distance; runs 4.5 hours - Low for extended run time: 1,300 lumens; 11,600 candela; 215m beam distance; runs 10 hours Indefinite run time with 12V DC power cord	<b>Vehicle Mount System</b> – International safety orange; includes vehicle-mountable hard-wire rack and shoulder strap  Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position
High impact ABS thermoplastic housing; rubberized impact bumper and lens ring, and reinforced D-rings	12.3 in. (31 cm); 10.4 lbs (4.7 kg)  Limited lifetime warranty Visit <a href="http://www.streamlight.com">www.streamlight.com</a> for full warranty information  See reverse for system configurations