

PRODUCT FACT SHEET

ProTac® HL HIGH LUMEN LITHIUM TACTICAL FLASHLIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION: With 600 lumens of blinding light, the ProTac® HL is the brightest addition to the ProTac® series. The

> ProTac® HL offers the latest in power LED technology and three different user selectable programs. The combination of small size and output from the C4® LED result in one of the brightest tactical personal carry

lights for its' size. Packaged with a removable pocket clip and holster.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Pink.

DIMENSIONS: Length: 5.40 in. (13.72 cm) Barrel Diameter: 1.0 in. (2.54 cm)

Head Diameter: 1.375 in. (3.49 cm) Tri-Lobe Diameter: 1.45 in. (3.68 cm)

WEIGHT: 5.6 oz (158 grams) with batteries

LENS: Glass lens, o-ring sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

See chart. Optimized electronics provides regulated intensity.

ON/OFF:

Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP™ programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.

RUN TIME:

BATTERY:



See chart. All claims to 10% of initial lumen output. Strobe: 2.5 continuous hours.

Two (2) 3 Volt CR123A Lithium batteries. CR123A batteries have a shelf life of 10 years.

FEATURES: C4® LED technology for extreme brightness.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

1 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

TEN-TAP™ programmable switch allows user to select one of three different programs.

Anti-roll facecap. Removable pocket clip.

Serialized for positive identification.

Streamlight's Limited Lifetime Warranty **WARRANTY:**

Meets applicable European Community directives. ϵ **APPROVALS:**

OPTIONAL

ACCESSORIES: Holster

> 600 OUTPUT LUMENS LUMENS **RUNTIME** 18h Ih 15min DISTANCE 253m 57m INTENSITY 16.000cd 800cd

> > Strobe Runtime: 2.5 hours

ProTac HL PERFORMANCE CURVE 600 60 HOURS

All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 12/18/2015 Revised: Rev: 0