



PRODUCT FACT SHEET

DUALIE WAYPOINT®

HIGH PERFORMANCE SPOT AND AREA LIGHT

MARKET

APPLICATIONS: Consumer, Law Enforcement, Search and Rescue, Security, Sporting Goods, Hardware/Tool

DESCRIPTION:

The Dualie Waypoint® light offers dual light technology with a forward facing spot beam and a bottom facing flood light that can be used individually or at the same time. It exhibits long runtime using 4 “C” sized alkaline batteries, high, medium and low intensity modes, and the latest in power LED technology. The spotlight provides a high powered beam for distance spotting and the bottom/downcast light for all your area lighting needs. The ergonomic handle hooks over any door, pipe, bar, cable or ladder rung for hands free operation. It also includes other innovative features like the D ring and kickstand to make the light perfect for any lighting need. The light is sealed and floats, so it’s great for wet applications.

CASE MATERIAL:

High impact polycarbonate housing. Rubberized lens cover. Available in yellow/black.

DIMENSIONS:

Length: 6.75 in. (17.14 cm) Height: 6.5 in. (16.5 cm) Head Diameter: 3.55 in. (9.0 cm)

WEIGHT:

2.06 lbs (934 grams) with batteries 1.41 lbs (640 grams) without batteries

LENS:

Unbreakable polycarbonate lens, o-ring sealed.

LIGHT SOURCE:

C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

High, Medium or Low output modes.

Both light sources -

High - 1000 Lumens and 3 hour run time.

Medium - 600 Lumens and 6 hour run time.

Low - 75 Lumens and 55 hours run time.

Front light only -

High - 750 Lumens, 75,000 candela peak beam intensity, 548 meter beam distance and 3.5 hour runtime.

Medium - 500 Lumens, 45,000 candela peak beam intensity, 426 meter beam distance and 6 hour run time.

Low - 35 Lumens, 3,200 candela peak beam intensity, 113 meter beam distance and 125 hour run time.

Side light only -

High - 500 Lumens, 250 candela peak beam intensity, 31 meter beam distance and 5.00 hour run time.

Medium - 230 Lumens, 120 candela peak beam intensity, 22 meter beam distance and 12.5 hour run time.

Low - 25 Lumens, 10 candela peak beam intensity, 6 meter beam distance and 170 hour run time.

ON/OFF:

Push button switch with momentary and click on operation. Using the momentary switch function, tap once for high, twice for medium and three times for low.

The rotary switch behind the button selects the main/front beam, bottom/area light, or both for a combination of distance and path way lighting in one setting.

RUN TIME:

All claims to 10% of initial lumen output.

BATTERY:

Four (4) “C” sized alkaline batteries. (not included with purchase)

FEATURES:

C4® LED technology for extreme brightness.

LED Solid State Power Regulation provides maximum light output throughout battery life.

IPX7 rated design.

2 meter impact resistance tested.

Integrated stand and D ring for hands-free lighting.



WARRANTY:

Streamlight's Limited Life Time Warranty

APPROVALS:

Meets applicable European Community directives.

OPTIONAL

ACCESSORIES:

N/A