

## 3AA HAZ-LO® HEADLIGHT - DIVISION 1 ALKALINE BATTERY-POWERED HEADLAMP

**MARKET**

**APPLICATIONS:** Industrial Safety, Public Works & Utilities, Law Enforcement, Hardware/Tool, Automotive, Marine, Sporting Goods, and Consumer.

**DESCRIPTION:** The 3AA Haz-Lo® is a compact, long running, high performance LED headlight. This headlight has been engineered to meet the stringent requirements of Division 1 hazardous locations, while maintaining exceptional light output and run time. The headlight is packaged with an elastic head strap and a rubber hard hat strap.

**CASE MATERIAL:** Impact resistant engineering resin case offering exceptional durability and weather resistance. All openings are O-ring sealed. Available in yellow.

**DIMENSIONS:** Face cap diameter: 1.88 in. (4.76 cm)  
Maximum headlight width 2.50 in. (6.35 cm)  
Maximum headlight length 3.08 in. (7.82 cm)

**WEIGHT:** 7.1 oz (202 grams) with batteries and head strap (batteries included with purchase).

**LENS:** Unbreakable polycarbonate lens.

**LIGHT SOURCE:** C4® LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** 120 Lumens measured system output, 6,800 candela peak beam intensity, and 165 meter beam distance.



**ON/OFF:** Push button switch - on/off operation.  
Rubber dome actuator provides easy operation even when wearing heavy gloves.

**RUN TIME:**  11 hours. All runtime claims are to 10% of initial lumen output.

**BATTERY:** Three (3) "AA" size alkaline batteries.

**FEATURES:** C4® LED technology for extreme brightness.  
Impact resistant housing - 1 meter drop test verified.  
Parabolic reflector produces long range brilliance and smooth uniform beam pattern.  
Package includes both elastic head strap and rubber hard hat strap.



**APPROVALS\*:**  UL Classified Class 1, Division 1, Groups A,B,C,D;  
Class II, Division 1, Groups E,F,G; Class III, Temperature Code: T4

 Meets applicable European Community Directives.

 ATEX: II 1G Ex ia IIC T3 Ga - FTZU 11 ATEX 0052X

 Permissible Portable Headlight Assembly; Approval No. 20-A070001-0  
Tested for use in Methane-air mixtures only.

 Ex ia IIC T3 Ga; UL-BR 12.0403X

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** N/A

\* See product for specific ratings.

All performance claims to ANSI/NEMA FL1-2009 Standard

Issued: 11/03/2006

Revised: 08/21/2015 Rev: 7

Engineered In the USA.  
Made in China.

Document #161

