

ProTac® 90
HIGH LUMEN TACTICAL LIGHT

MARKET
APPLICATIONS: Law Enforcement, Security, Military, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION: Lightweight, compact, high lumen, CR123 Lithium or AA battery powered 90 degree Tactical Light featuring the latest in shock-proof power LED technology and three different user selectable programs. The combination of size, output, and battery versatility, result in one of the brightest and versatile lights. Packaged with a removable pocket clip, CR123 and AA alkaline battery.

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish.

DIMENSIONS: Length: 3.78 in. (9.6 cm) Head diameter: 1.05 in. (2.67 cm) Barrel diameter: .86 in. (2.18 cm)

WEIGHT: 2.8 oz (79 grams) with CR123 battery (included in purchase).
3.1 oz (88 grams) with AA alkaline battery (included in purchase).
2.7 oz (77 grams) with AA Lithium battery.

LENS: High temperature, shock mounted, AR coated, impact resistant borofloat glass.

LIGHT SOURCE: C4®LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: **CR123 Battery:** 5,400 candela peak beam intensity, 147m beam distance, 300 lumens measured system output on High. 700 candela peak beam intensity, 53m beam distance, 40 lumens measured system output on Low.

AA Alkaline or AA Lithium Battery: 2,150 candela peak beam intensity, 93m beam distance, 125 lumens measured system output on High. 700 candela peak beam intensity, 53m beam distance, 40 lumens measured system output on Low.

ON/OFF: Multi-function, push-button tactical switch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.

RUN TIME:  1h 45min

CR123 - High 1 hour 45 minutes, Low 14 hours, Strobe 2.5 hours.

AA Alkaline - High 2 hour 45 minutes, Low 8 hours 15 minutes, Strobe 3.5 hours.

AA Lithium - High 5 hours 30 minutes, Low 15 hours, Strobe 8 hours.

Run times are to 10% of initial output. Solid-state current regulation for consistent illumination.

BATTERY: One 3 Volt CR123A lithium battery (with a storage life of 10 years), one AA Alkaline battery, or one AA Lithium Battery.

FEATURES:


C4®LED technology for extreme brightness.

IPX7 rated design; water proof to 1 meter for 30 minutes

2 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.

Momentary/steady On-Off switch.

TEN-TAP® programmable switch allows user to select one of three different programs.

Serialized for positive identification.

Removable pocket clip.

APPROVALS: Meets applicable European Community Directives. **CE**
WARRANTY: Streamlight's Limited Lifetime Warranty.

OPTIONAL
ACCESSORIES: None
